



www.sealking.ca

BEFORE

AFTER



BRICK AND BLOCK ADHESIVE - DATA SHEET

DESCRIPTION

Seal King's Brick & Block is specially designed for use in installing landscape blocks, steps and retaining walls. Bonds to brick block, stone, slate, metal, and wood. Minimizes movement after application and helps maintain structure stability.

DIRECTIONS FOR APPLICATION

All surfaces must be structurally sound, clean, dry, and free of mud, dirt, dust, ice and other foreign substances that will affect product adhesion. Precut materials and clean surfaces prior to using adhesive. Old concrete or surfaces must be cleaned with appropriate cleaning solution and dried thoroughly.

- Cut spout to desired bead size and puncture seal inside spout. 1/4" min. to 3/8" max.
- For installing landscape blocks and retaining caps apply 1/4" beads adhesive 2" in from the front and back edges. When installing cement pavers or steps apply "S" shaped beads to the back surfaces to be bonded directly to the concrete.
- Do not apply more adhesive than can be bonded in 10-15 minutes.
- Avoid foot traffic on paver stones and retaining caps for a minimum of 24-48 hours. Do not allow heavy traffic for 4-5 days.
- Clean up wet adhesive with soap and water. Dried adhesive, use mineral spirits or a non-flammable adhesive remover.

CAUTION

- Apply only at temperatures above 5C (40°F). Not recommended for pool coping or water features.
- Not recommended for areas of continuous water submersion or plastic.
- Avoid contact with eyes and skin.
- Keep out of reach of children.

PLEASE NOTE

- If adhesive is exposed to sunlight it must be covered or painted. \

COVERAGE

- 3/8" bead=14 lin.ft/ cartridge

SIZES AVAILABLE:

300ml and 825ml