



www.sealking.ca

BEFORE

AFTER



WATER BASED PAVING STONE SEALER - DATA SHEET

DESCRIPTION

Seal King's High Performance Concrete Sealer is a one component water based sealer acrylic urethane system. It is specially formulated to penetrate deep into the concrete and protect the surface from all types of weathering and harsh chemicals. This low odor sealer contains 20% solids and is available in low and high gloss.

BENEFITS

- Acrylic/urethane emulsion for increased durability.
- Low odor, water based.
- Touch dry in 1 hour.
- One 5 gal pail covers approximately 1000 sq. ft.
- Protects against: Motor oil, gas, salt, anti-freeze, transmission fluid, and dirt.

DIRECTIONS FOR APPLICATION

- Remove any oil, dirt and other contaminants with Seal King's cleaners.
- Make sure area to be sealed is dry and clean.
- Apply with roller, brush or spray pump.
- Allow 1 hour for walking and 24 hours for parking.

CAUTION

- Protect from freezing.
- Avoid inhalation.
- Keep away from children.
- Avoid Skin and eye contact. If contact occurs wash with cold water.

COVERAGE

Approximately 200 sq. ft./1 gal.

V.O.C. COMPLIANT

Product meets V.O.C. contents in accordance to E.P.A. 40 CFR pt 59 table I subpart D for Concrete Curing & Sealing Compounds with maximum V.O.C. content of **100 G/L.**

SHELF LIFE

Water Based materials have a shelf life of 1 (one) year.

SIZES AVAILABLE:

FINISHES:

OIL BASED:

OIL BASED FINISHES:

5 gal. (18.9 Ltr), 1 gal. (3.8 Ltr)

Natural look, Semi-gloss,
High-gloss

Available

Natural look, Semi-gloss,
High-gloss